

County Surveyor's Record, Douglas County, Oregon

Subdivision of T. 29 S., R. 2 W.

CHAINS	<p>marked $\frac{1}{4}$ S 14 B T.</p> <p>A fir, 22 ins. diam., bears S.64*30'W., 27 lks. dist., marked $\frac{1}{4}$ S 15 B T.</p> <p>42.00 Descend NE. slope.</p> <p>47.60 Creek, 1 lk. wide, course SE.</p> <p>50.26 Creek, 2 lks. wide, course SE.; ascend.</p> <p>59.30 Top of butte; descend NE. slope.</p> <p>68.00 Foot of descent; ascend SE. slope.</p> <p>70.50 Top of spur ridge, bears NW. and SE.; descend.</p> <p>80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 10, 11, 14 and 15, with brass cap marked</p> <div style="text-align: center;"> <table border="1"> <tr><td>T29S</td><td>R2W</td></tr> <tr><td>S10</td><td>S11</td></tr> <tr><td>S15</td><td>S14</td></tr> <tr><td colspan="2">1917</td></tr> </table> </div> <p>from which</p> <p>A hemlock, 9 ins. diam., bears N.9*E., 14 lks. dist., marked T 29 S R 2 W S 11 B T.</p> <p>A fir, 20 ins. diam. bears S.8*E., 11 lks. dist., marked T 29 S R 2 W S 14 B T.</p> <p>A fir, 10 ins. diam., bears S.63*W., 39 lks. dist., marked T 29 S R 2 W S 15 B T.</p> <p>A fir, 18 ins. diam., bears N.51*W., 22 lks. dist., marked T.29 S R 2 W S 10 B T.</p> <p>Land, mountainous.</p> <p>Soil, dark loam, 2 ins. deep on clay subsoil, 2nd and 3rd rate.</p> <p>Timber, fir, pine, hemlock and cedar.</p> <p>Undergrowth, rhododendron, chinquapin and maple.</p>	T29S	R2W	S10	S11	S15	S14	1917	
T29S	R2W								
S10	S11								
S15	S14								
1917									
40.00	<p>N.89*58'E., on a random line, bet. secs. 11 and 14.</p> <p>Set temp. $\frac{1}{4}$ sec. cor.</p>								
80.08	<p>Intersect the N. and S. line, 12 lks. S. of the cor. of secs. 11,12,13 and 14.</p> <p>Thence</p> <p>S.89*53'W., on a true line, bet. secs. 11 and 14.</p>								