

6260
17/

County Surveyor's Record, Douglas County, Oregon

Subdivision of T. 29 S., R. 2 W.

CHAINS

ground, for $\frac{1}{4}$ sec. cor., with brass cap marked

$\frac{1}{4}$
S10 | S11
1917

from which

A fir, 10 ins. diam., bears N.72*30'E., 9 lks. dist.,
marked $\frac{1}{4}$ S 11 B T.

A fir, 10 ins. diam., bears N.48*30'W., 9 lks. dist.,
marked $\frac{1}{4}$ S 10 B T.

Along SE. slope.

55.80 Creek, 4 lks. wide, course SE.; ascend.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the
ground, for cor. of secs. 2, 3, 10 and 11, with brass
cap marked

T29S R2W
S3 | S2
S10 | S11
1917

from which

A fir, 16 ins. diam., bears N.50*30'E., 26 lks. dist.,
marked T 29 S R 2 W S 2 B T.

A fir, 10 ins. diam., bears S.28'E., 35 lks. dist.,
marked T 29 S R 2 W S 11 B T.

A fir, 12 ins. diam., bears S.74*W., 13 lks. dist.,
marked T 29 S R 2 W S 10 B T.

A pine, 6 ins. diam., bears N.17*W., 27 lks., dist.,
marked T 29 S R 2 W S 3 B T.

Land, mountainous and rolling.

Soil, gravelly loam, 2nd and 3rd rate.

Timber, fir, pine, hemlock and cedar.

Undergrowth, rhododendron, maple and chinquapin.

40.00 N.89*53'E., on a random line, bet. secs. 2 and 11.
Set temp. $\frac{1}{4}$ sec. cor.

80.24 Intersect the N. and S. line, 33 lks. N. of the cor. of
secs. 1, 2, 11 and 12.

Thence