

County Surveyor's Record, Douglas County, Oregon

Subdivision of T. 29 S., R. 2 W.

CHAINS

Ascend through heavy timber and dense undergrowth.

8.20 Top of spur, slopes SE.; descend.

19.40 Creek, 3 lks. wide, course E.

21.40 Creek, 5 lks. wide, course SE.; ascend.

26.05 Mining ditch. course SE.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked
$$\begin{array}{c} \frac{1}{4} \\ \text{S28} | \text{S27} \\ \hline 1917 \end{array}$$

from which

A fir, 12 ins. diam., bears N.63*30'E., 20 lks. dist., marked $\frac{1}{4}$ S 27 B T.

A fir, 30 ins. diam., bears N.13*15'W., 90 lks. dist., marked $\frac{1}{4}$ S 28 B T.

44.00 Top of spur, slopes SW.; continue ascent.

70.00 Top of ridge, bears NW. and SE.; descend.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 21, 22, 27 and 28, with brass cap marked

$$\begin{array}{c} \text{T29S R2W} \\ \text{S21} | \text{S22} \\ \hline \text{S28} | \text{S27} \\ 1917 \end{array}$$

from which

A fir, 16 ins. diam., bears N.20*30'E., 66 lks. dist., marked T 29 S R 2 W S 22 B T.

A fir, 10 ins. diam., bears S.52'E., 9 lks. dist., marked T 29 S R 2 W S 27 B T.

A fir, 10 ins. diam., bears S.49*30'W., 38 lks. dist., marked T 29 S R 2 W S 28 B T.

A fir, 16 ins. diam., bears N.15'W., 39 lks. dist., marked T 29 S R 2 W S 21 B T.

Land, mountainous.

Soil, rocky, 3rd rate:

Timber, fir, pine and cedar.

Undergrowth, maple, rhododendron, chinquapin and salal.