

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 29 S., R. 2 W.

CHAINS	<p>ground, for $\frac{1}{4}$ sec. cor., with brass cap marked</p> <p style="text-align: center;">$\frac{1}{4}$ S21 S22 1917</p> <p>from which</p> <p>A fir, 30 ins. diam., bears N.66*30'E., 80 lks. dist., marked $\frac{1}{4}$ S 22 B T.</p> <p>A fir, 30 ins. diam., bears N.39*45'W., 70 lks. dist., marked $\frac{1}{4}$ S 21 B T.</p> <p>40.80 Top of spur, slopes NE.; descend.</p> <p>44.30 Draw, course E.; ascend.</p> <p>50.20 Draw, course E.; continue ascent.</p> <p>55.00 Top of spur, slopes E.; descend.</p> <p>68.80 Creek, 1 lk. wide, course SE.; ascend.</p> <p>77.80 Top of spur, slopes SE.; descend.</p> <p>80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 15, 16, 21 and 22, with brass cap marked</p> <p style="text-align: center;">T29S R2W S16 S15 S21 S22 1917</p> <p>from which</p> <p>A cedar, 20 ins. diam., bears N.25*45'E., 58 lks. dist., marked T 29 S R 2 W S 15 B T.</p> <p>A fir, 42 ins. diam., bears S.25*15'E., 16 lks. dist., marked T 29 S R 2 W S 22 B T.</p> <p>A pine, 6 ins. diam., bears S.12*15'W., 68 lks. dist., marked T 29 S R 2 W S 21 B T.</p> <p>A fir, 40 ins. diam., bears N.43*15'W., 70 lks. dist., marked T 29 S R 2 W S 16 B T.</p> <p>Land, mountainous.</p> <p>Soil, rocky, 3rd rate.</p> <p>Timber, fir, pine and cedar.</p> <p>Undergrowth, maple, rhododendron, young timber and salal.</p>
40.00	<p>N.89*51'E., on a random line, bet. secs. 15 and 22.</p> <p>Set temp. $\frac{1}{4}$ sec. cor.</p>