

County Surveyor's Record, Douglas County, Oregon

Subdivision of T. 29 S., R. 2 W.

CHAINS	<p>A fir, 36 ins. diam., bears N.27*30'E., 42 lks. dist., marked $\frac{1}{4}$ S 15 B T.</p> <p>A fir, 18 ins. diam., bears N.40*15'W., 94 lks. dist., marked $\frac{1}{4}$ S 16 B T.</p> <p>47.40 Creek, 1 lk. wide, course SW.</p> <p>69.40 Top of spur, slopes W., along W. slope.</p> <p>75.30 Spring branch, course SW.</p> <p>80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 9, 10, 15 and 16, with brass cap marked</p> <div style="text-align: center;"> <table border="1"> <tr> <td colspan="2">T29S R2W</td> </tr> <tr> <td>S9</td> <td>S10</td> </tr> <tr> <td>S16</td> <td>S15</td> </tr> <tr> <td colspan="2">1917</td> </tr> </table> </div> <p>from which</p> <p>A fir, 12 ins. diam., bears N.43*E., 23 lks. dist., marked T 29 S R 2 W S 10 B T.</p> <p>A fir, 22 ins. diam., bears S56*30'E., 67 lks. dist., marked T 29 S R 2 W S 15 B T.</p> <p>A fir, 12 ins. diam., bears S.30*30'W., 30 lks. dist., marked T 29 S R 2 W S 16 B T.</p> <p>A fir, 16 ins. diam., bears N.78*45'W., 63 lks. dist., marked T 29 S R 2 W S 9 B T.</p> <p>Land, mountainous</p> <p>Soil, gravelly, 3rd rate.</p> <p>Timber, fir, hemlock and cedar.</p> <p>Undergrowth, maple, rhododendron, and young timber.</p> <hr/> <p>N.89*48'E., on a random line, bet. secs. 10 and 15.</p> <p>40.00 Set temp. $\frac{1}{4}$ sec. cor.</p> <p>80.06 Intersect the N. and S. line, 2 lks. N. of the cor. of Secs. 10, 11, 14 and 15.</p> <p>Thence</p> <p>S.89*49'W., on a true line, bet. secs. 10 and 15.</p> <p>Ascend through heavy timber and dense undergrowth.</p> <p>23.30 Top of spur ridge, bears NW. and SE.; descend.</p> <p>28.00 Head of draw, course SE.; ascend.</p>	T29S R2W		S9	S10	S16	S15	1917	
T29S R2W									
S9	S10								
S16	S15								
1917									