

6270
82
County Surveyor's Record, Douglas County, Oregon

Subdivision of T. 29 S., R. 2 W.

CHAINS	<p>A balsam fir, 12 ins. diam., bears N.38*E., 62 lks. dist., marked T 29 S R 2 W S 3 B T.</p> <p>A fir, 12 ins. diam., bears S.18*E., 46 lks. dist., marked T 29 S R 2 W S 10 B T.</p> <p>A fir, 12 ins. diam., bears S.22*W., 44 lks. dist., marked T 29 S R 2 W S 9 B T.</p> <p>A fir, 15 ins. diam., bears N.56*W., 32 lks. dist., marked T 29 S R 2 W S 4 B T.</p> <p>Land, mountainous.</p> <p>Soil, gravelly and rocky, 3rd rate.</p> <p>Timber, fir, pine, hemlock and cedar.</p> <p>Undergrowth, rhododendron, chinquapin, maple and young timber.</p>
40.00	<p>N.89*49'E., on a random line, between secs. 3 and 10</p> <p>Set temp. $\frac{1}{4}$ sec. cor.</p>
80.04	<p>Intersect the N. and S. line, 9 lks. S. of the cor. of secs. 2, 3, 10 and 11.</p> <p>Thence</p> <p>S.89*45'W., on a true line, bet. secs. 3 and 10.</p> <p>Descend through heavy timber and dense undergrowth.</p>
14.30	<p>Deadman creek, 4 lks. wide, course SE.; ascend.</p>
23.00	<p>Top of spur ridge, bears NW. and SE.; descend.</p>
40.02	<p>Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked</p> $\frac{\frac{1}{4} \frac{S3}{S10}}{1917}$ <p>from which</p> <p>A balsam fir, 10 ins. diam., bears S.53*30'E., 27 lks dist., marked $\frac{1}{4}$ S 10 B T.</p> <p>A balsam fir, 9 ins. diam., bears N.43*W., 29 lks. dist., marked $\frac{1}{4}$ S 3 B T.</p>
40.40	<p>Creek, 1 lk. wide, course SE.; ascend.</p>
77.30	<p>Top of ridge, bears N. and S.; descend.</p>
80.04	<p>The cor. of secs. 3, 4, 9 and 10.</p>