

County Surveyor's Record, Douglas County, Oregon

Subdivision of T. 29 S., R 2 W.

CHAINS

- A fir, 42 ins. diam., bears S.40°E., 16 lks. dist., marked T 29 S R 2 W S 28 B T.
- A fir, 60 ins. diam., bears S.9°W., 18 lks. dist., marked T 29 S R 2 W S 29 B T.
- A fir, 50 ins. diam., bears N.60°30'W., 58 lks. dist., marked T 29 S R 2 W S 20 B T.

Land, mountainous.
 Soil, light gravelly and rocky loam, 3rd rate.
 Timber, fir, pine, cedar and hemlock.
 Undergrowth, maple, young timber and salal.

- N.89°49'E., on a random line, bet. secs. 21 and 28.
- 40.00 Set temp. $\frac{1}{4}$ sec. cor.
- 79.78 Intersect the n. and S. line, at the cor. of secs. 21, 22, 27 and 28.

Thence.
 S.89°49'W., on a true line, bet. secs. 21 and 28.
 Ascend through heavy timber and dense undergrowth.

- 12.00 Top of ridge, bears NW. and SE.; descend.
- 23.80 Draw, course S.; ascend.
- 29.00 Top of spur, slopes Sw.; descend.
- 39.89 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked.

$$\begin{array}{r} \frac{1}{4} \text{ S21} \\ \hline \text{S28} \\ 1917 \end{array}$$

from which
 A fir, 40 ins. diam., bears N.65°E., 17 lks. dist., marked $\frac{1}{4}$ S 21 B T.
 A yew, 8 ins. diam., bears S.69°45'W., 23 lks. dist., marked $\frac{1}{4}$ S 28 B T.

- 39.98 Creek, 1 lk. wide, course S.; ascend.
- 46.00 Top of spur, slopes S.; descend.
- 61.70 Spring branch, course S.
- 64.50 Creek, 4 lks. wide, course SE.; ascend.
- 74.50 Top of spur, slopes N.; descend.