

County Surveyor's Record, Douglas County, Oregon

6277  
89

Subdivision of T. 29 S., R. 2 W.

CHAINS

Soil, light, loose, gravelly loam, 3rd rate.  
Timber, fir, cedar, hemlock and pine.  
Undergrowth, maple, rhododendron, chinquapin and young timber.

N.0°06'E., bet. secs. 16 and 17.

Ascend through heavy timber and dense undergrowth.

18.00 Top of spur, slopes SE.; continue ascent.

40.00 Set and iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap marked

$\frac{1}{4}$   
 S17 | S16  
 1917

from which

A fir, 20 ins. diam., bears S.52°30'W., 76 lks. dist., marked  $\frac{1}{4}$  S 17 B T.

A fir, 36 ins. diam., bears N.48°E., 61 lks. dist., marked  $\frac{1}{4}$  S 16 B T.

45.60 Top of ridge, bears NW. and SE.; descend.

54.80 Draw, course SE.; ascend.

67.00 Top of spur, slopes SE.; descend.

78.00 Draw, course NE.; ascend.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 8, 9, 16 and 17, with brass cap marked

T29S R2W  
 S8 | S9  
 S17 | S16  
 1917

from which

A fir, 40 ins. diam., bears N.42°E., 60 lks. dist., marked T 29 S R 2 W S 9 B T.

A hemlock, 8 ins. diam., bears S.65°E., 65 lks. dist., marked T 29 S R 2 W S 16 B T.

A hemlock, 7 ins. diam., bears S.45°W., 58 lks. dist., marked T 29 S R 2 W S 17 B T.

A fir, 36 ins. diam., bears N.9°30'W., 41 lks. dist., marked T 29 S R 2 W S 8 B T.