

6282
94

County Surveyor's Record, Douglas County, Oregon

Subdivision of T. 29 S. R 2 W.

CHAINS

from which

A fir, 14 ins. diam., bears N.29°E., 42 lks. dist.,
marked T 29 S R 2 W S 29 B T.

A hemlock, 6 ins. diam., bears S.2°45'E., 29 lks. dist.,
marked T 29 S R 2 W S 32 B T.

A fir, 6 ins. diam., bears S.31°45'W., 13 lks. dist.,
marked T 29 S R 2 W S 31 B T.

A hemlock, 6 ins. diam., bears N.75°W., 22 lks. dist.,
marked T 29 S R 2 W S 30 B T.

Land, mountainous.

Soil, gravelly, 3rd rate.

Timber, fir, cedar, pine and hemlock.

Undergrowth, snowbrush, maple, rhododendron and young
timber.

N.89°54'E., on a random line, bet. secs. 29 and 32.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

79.68 Intersect the N. and S. line, 18 lks. S. of the cor. of
secs. 28, 29, 32 and 33.

Thence.

S.89°46'W., on a true line, bet secs. 29 and 32.

Ascend SE. slope, through heavy timber and dense undergrowth.

26.00 U.S. Forest Service trail and telephone line, Tiller to
Peel, bears N. and S.

32.25 Top of ridge, bears N. and S.; descend.

39.84 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the
ground, for $\frac{1}{4}$ sec. cor., with brass cap marked

$$\frac{\frac{1}{4} \text{ S29}}{\text{S32}} \\ 1917$$

from which

A fir, 15 ins. diam., bears N.5°E., 58 lks. dist.,
marked $\frac{1}{4}$ S 29 B T.

A fir, 16 ins. diam., bears S.11°45'W., 63 lks. dist.,
marked $\frac{1}{4}$ S 32 B T.

70.60 Top of spur, slopes SW.; continue descent.