

County Surveyor's Record, Douglas County, Oregon

Subdivision of T. 29 S., R. 2 W.

CHAINS	<p>Descend through heavy timber and dense undergrowth.</p> <p>4.94 Creek, 1 lk. wide, course SW.; ascend.</p> <p>22.90 Top of spur, slopes E.; descend.</p> <p>29.60 Draw, course SE.; ascend.</p> <p>40.00 Top of spur, slopes SE.</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 26 ins in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked</p> <div style="text-align: center; margin: 10px 0;"> $\begin{array}{c} \dagger \\ \text{S30} \text{S29} \\ \hline 1917 \end{array}$ </div> <p>from which</p> <p style="padding-left: 40px;">A fir, 15 ins. diam., bears S.87°E., 66 lks. dist., marked $\frac{1}{4}$ S 29 B T.</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears S.9°15'W., 25 lks. dist., marked $\frac{1}{4}$ S 30 B T.</p> <p>Along E. slope.</p> <p>69.50 Top of ridge, bears NE. and SW.; descend.</p> <p>80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 19, 20, 29 and 30, with brass cap marked</p> <div style="text-align: center; margin: 10px 0;"> $\begin{array}{c} \text{T29S R2W} \\ \text{S19} \text{S20} \\ \hline \text{S30} \text{S29} \\ \hline 1917 \end{array}$ </div> <p>from which</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears N.27°45'E., 27 lks. dist., marked T 29 S R 2 W S 20 B T.</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears S.23°30'E., 76 lks. dist., marked T 29 S R 2 W S 29 B T.</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears S.57°30'W., 10 lks. dist., marked T 29 S R 2 W S 30 B T.</p> <p style="padding-left: 40px;">A fir, 15 ins. diam., bears N.55°30'W., 79 lks. dist., marked T 29 S R 2 W S 19 B T.</p> <p>Land, mountainous.</p> <p>Soil, rocky and gravelly, 3rd rate.</p> <p>Timber, fir, cedar and hemlock.</p> <p>Undergrowth, maple and rhododendron.</p>
--------	--