

## Subdivision of T. 29 S., R. 2 W.

## CHAINS

N.89\*53'E., on a true line, bet, secs. 19 and 30.  
 Descend through heavy timber and dense undergrowth.  
 9.80 Draw, course SE.; ascend.  
 24.40 Top of spur, slopes SE.; descend.  
 44.40 Creek, 2 lks. wide, course SE.  
 46.71 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
 ground, for  $\frac{1}{4}$  sec. cor., with brass cap marked

$$\begin{array}{r} \frac{1}{4} \text{ S19} \\ \hline \text{S30} \\ 1917 \end{array}$$

from which

A hemlock, 12 ins. diam., bears N.30\*E., 61 lks. dist.,  
 marked  $\frac{1}{4}$  S 19 B T.

A Fir, 48 ins. diam., bears S.62\*W., 21 lks. dist.,  
 marked  $\frac{1}{4}$  S 30 B T.

48.70 Coffee Creek, 5 lks. wide, course S.; ascend.  
 69.00 Top of spur, slopes NW.; descend.  
 80.90 Draw, course NW.; ascend.  
 84.70 Top of spur, slopes NW.; descend.  
 86.71 The cor. of secs. 19, 20, 29 and 30.  
 Land, mountainous  
 Soil, loose gravelly loam, 3rd rate.  
 Timber, fir, pine, cedar and hemlock.  
 Undergrowth, maple, chinquapin and young timber.

N.0\*05'E., bet secs. 19 and 20  
 Descend through heavy timber and dense undergrowth.  
 8.00 Draw, course W.; ascend.  
 13.40 Top of spur, slopes W.; descend.  
 18.00 Draw, course W.; ascend.  
 25.90 Top of spur, slopes NW.; along W. slope.  
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
 ground, for  $\frac{1}{4}$  sec. cor., with brass cap marked

$$\begin{array}{r} \frac{1}{4} \\ \text{S19} \text{ S20} \\ 1917 \end{array}$$

from which