

6290  
107

County Surveyor's Record, Douglas County, Oregon

Subdivision of T. 29 S., R. 2 W.

CHAINS

marked T 29 S R 2 W S 8 B T.

A fir, 16 ins. diam., bears S.25\*30'E., 6 lks. dist.,

marked T 29 S R 2 W S 17 B T.

A fir, 16 ins. diam., bears S.34\*30'W., 52 lks. dist.,

marked T 29 S R 2 W S 18 B T.

A fir, 30 ins. diam., bears N.34\*30'W., 24 lks. dist.,

marked T.29 S R 2 W S 7 B T.

Land, mountainous.

Soil, gravelly, 3rd rate.

Timber, fir, cedar and hemlock.

Undergrowth, rhododendron, maple and chinquapin.

N.89\*43'E., on a random line, bet. secs. 8 and 17.

40.00 Set temp.  $\frac{1}{4}$  sec. cor.

80.00 Intersect the N. and S. line, 5 lks. S. of the cor. of  
secs. 8, 9, 16 and 17.

Thence

S.89\*41'W., on a true line, bet. secs. 8 and 17.

Ascend through heavy timber and dense undergrowth.

20.30 Top of ridge, bears N. and S.; descend.

25.00 U.S. Forest Service trail, and telephone, line, Tiller to  
Peel, bears NE. and SW.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
ground, for  $\frac{1}{4}$  sec. cor., with brass cap marked.

$\frac{S8}{S17}$   
 1917

from which

A fir, 36 ins. diam., bears N.2\*W., 36 lks. dist.,  
marked  $\frac{1}{4}$  S 8 B T.

A hemlock, 7 ins. diam., bears S12\*45'E., 62 lks.  
dist., marked  $\frac{1}{4}$  S 17 B T.

50.00 Top of spur, slopes NW.; along S. slope.

80.00 The cor. of secs. 7, 8, 17 and 18.

Land, mountainous.

Soil, light gravelly loam, 3rd rate.