

County Surveyor's Record, Douglas County, Oregon

Exteriors of T. 29 S., R. 3 W.
as surveyed by W. H. Byars, Deputy Surveyor,
under contract No. 376, dated January 22, 1881.

West Boundary.

CHAINS

Begin at the corner established for corner to sections 7, 12, 13 and 18. Set new post witness trees all standing viz.

A red fir, 48 ins. diam., bears S.25*E., 20 lks.

A yew, 6 ins. diam., bears N.47*E., 27 lks.

A yew, 6 ins. diam., bears N.25*W., 19 lks.

A fir, 24 ins. diam., bears S.20*W., 15 lks.

North bet. secs. 7 and 12.

Va. 19*E.

38.92 $\frac{1}{4}$ sec. cor., witness trees standing viz.

A maple, 6 ins. diam., bears N.30*W., 25 lks.

A red fir, 10 ins. diam., bears S.55*E., 16 lks.

77.74 Cor. to secs. 1, 6, 7, and 12; bearing trees all standing, viz.

A maple, 10 ins. diam., bears S.57*E., 35 lks.

A red fir, 10 ins. diam., bears N.40*E., 35 lks.

A cedar, 40 ins. diam., bears S.40*W., 9 lks.

A red fir, 12 ins. diam., bears N.50*W., 20 lks.

Land, mountainous, 2nd rate.

Timber, good; chiefly fir, cedar, hemlock and pine.

North, bet. secs. 1 and 6.

Va. 18*E.

32.00 Top of ridge ^{course} E. and W.

40.00 Unable to find old post or witness trees. Set new post,

A fir, ~~for~~ $\frac{1}{4}$ sec. cor. from which

A fir, 18 ins. diam., bears S.40*E., 26 lks.

A fir, 22 ins. diam., bears S.45*W., 19 lks.

68.60 Intersect South boundary of T. 28 S R 4 West 28.24 ^{chs.} lks.

West of Township corner.

Set hemlock post for Township corner, from which

A fir, 20 ins. diam., bears S.30*E., 61 lks.

A fir, 18 ins. diam., bears S.35*W., 34 lks.

Land, mountainous, 2nd rate.

Timber, good; chiefly fir, cedar, pine and hemlock.

April 6th, 1881.