

County Surveyor's Record, Douglas County, Oregon

37

Subdivisions of T. 29 S., R. 3 W.

CHAINS

A Laurel, 6 ins. diam., bears N.20*W., 14 lks.
dist.

79.63 To sec. cor.

Land, W. slope of mountain 2nd rate.

Timber, stunted Fir, Cedar, Pine and Laurel.

North, on Random line between Sections 1 and 2.

Va. 18*E.

40.00 Set temp. $\frac{1}{2}$ sec. cor.79.02 Intersect N. bdy. of T. 51 lks. W. of cor. to Secs. 1,
2, 35 and 36.

S.0*21*W., on True line between Secs. 1 and 2.

7.50 Enter open Pine timber.

38.00 Creek, 1 lk. wide, C. NW.

39.02 Set a Fir post for the $\frac{1}{2}$ sec. cor., from which

A Fir, 8 ins. diam., bears N.40*E., 9 lks. dist.

A Fir, 10 ins. diam., bears N.25*W., 18 lks. dist.

75.00 Top of spur, C. W.

79.02 To sec. cor.

Land, S. part mountainous; N. part rolling, 2nd rate.

Timber, chiefly Fir, Pine and Cedar.

April 22, 1881.

Begin at cor. to Sections 34 and 35.

South Boundary of Township and run thence

North, between Sections 34 and 35.

Va. 18*E.

12.50 Summit of mountain, C. W.