

County Surveyor's Record, Douglas County, Oregon

SUBDIVISIONS of T. 29 S., R. 4 W.

CHAINS

August 6, 1854.

North, between Secs. 34 and 35.

Var. 18½°E.

40.00 Set ¼ sec. post, from which +25

A B. Oak, 10 ins. diam., bears S.13°E., 33 lks. dist.

A B. Oak, 8 ins. diam., bears N.27°W., 63 lks. dist.

80.00 Set a post cor. of Secs. 26, 27, 34 and 35, from which +50

A B. Oak, 10 ins. diam., bears S.83°W., 33 lks. dist.

A B. Oak, 8 ins. diam., bears N.36°W., 42 lks. dist.

A B. Oak, 6 ins. diam., bears S.27°E., 30 lks. dist.

A B. Oak, 14 ins. diam., bears N.38°E., 82 lks. dist.

Soil, 3rd rate.
Land, High, Rolling.
Timber, Oak openings.

East, on Random between Secs. 26 and 35.

Var. 18°00'E.

40.00 Set temp. ¼ sec. post.

79.64 Intersect E. boundary, 28 lks. N. of Sec. cor.

S.89°48'W., on True line between Secs. 26 and 35.

39.82 Set ¼ sec. post at average dist., from which -50

A B. Oak, 8 ins. diam., bears S.68°W., 15 lks. dist.

A B. Oak, 14 ins. diam., bears N.67°E., 81 lks. dist.

79.64 To sec. cor.

Soil, 2nd rate.