

## County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 29 S., R. 4 W.

CHAINS		
	Va. $18\frac{1}{2}$ *E.	
	East, on a Random line bet. Secs. 29 and 32.	
40.00	Set temp. $\frac{1}{4}$ sec. post.	
80.60	Intersected E. boundary 70 lks. S. of sec. cor. S.89*30'W., on a true line between Secs. 29 and 32.	
40.30	Set $\frac{1}{4}$ sec. post at average dist., from which A B. Oak, 18 ins. diam., bears S.65*W., 66 lks. dist. A Laurel, 6 ins. diam., bears N.23*W., 32 lks. dist.	-50
45.00	A Cedar, 36 ins. diam.,	-10
80.60	To Section corner. Soil, 3rd rate. Land, high, rolling. Timber, Fir, Oak, Pine and Cedar. Underbrush, Oak and Laurel.	
	West, on Random line between Secs. 30 and 31.	
40.00	Set temp. $\frac{1}{4}$ sec. post.	
78.60	Intersect W. boundary 48 lks. S. of sec. cor. S.89*39 $\frac{1}{2}$ 'E., on True line between Secs. 30 and 31.	
38.60	Set $\frac{1}{4}$ sec. post at proper dist., from which A B. Oak, 24 ins. diam., bears N.55*W., 14 lks. dist. A B. Oak, 30 ins. diam., bears S.15*W., 40 lks. dist.	+30
78.60	To Section corner. Soil, 2nd rate. Land, high rolling. Timber, Oak openings.	
	North, between Secs. 29 and 30.	
40.00	Set $\frac{1}{4}$ sec. post, from which A Laurel, 4 ins. diam., bears N.55*E., 12 lks. dist. A Laurel, 4 ins. diam., bears N.25*W., 24 lks. dist.	-20