

County Surveyor's Record, Douglas County, Oregon

41

Subdivisions of T. 29 S., R. 4 W.

CHAINS

Beginning at the corner of Secs. 11, 12, 13 and 14

I run

West, on Random line between Secs. 11 and 14.

Var. 19°E.

40.00 Set temp. $\frac{1}{4}$ sec. cor.81.50 To a point 167 lks. North of established cor. to
Secs. 10, 11, 14 and 15.

Witness trees standing, viz:

A B. Oak, 8 ins. in diam., bears S.15°E., 130 lks.
dist.A B. Oak, 15 ins. diam., bears N.45°E., 209 lks.
dist.A B. Oak, 8 ins. diam., bears S.80°W., 450 lks.
dist.A B. Oak, 8 ins. diam., bears N.20°W., 440 lks.
dist.

No evidence of this line ever being run, thence

I run

N.88°48'E., on True line between Secs. 11 and 14.

6.00 Top of ridge, C. S.

40.75 Set Alder post for the $\frac{1}{4}$ sec. cor., from whichAn Alder, 6 ins. diam., bears S.10°E., 15 lks.
dist.A Maple, 4 ins. diam., bears N.15°W., 22 lks.
dist.

41.50 Creek, 15 lks. wide, C. S.

81.50 To sec. cor.

Land, mountainous, heavily timbered, 2nd rate.

Timber, chiefly Fir, Oak, Laurel, Cedar and Pine.

April 8, 1881.

North, between Secs. 10 and 11.

Var. 19°E.

25.00 Top of ridge, C. SE. and NW.

40.00 Set $\frac{1}{4}$ sec. cor. A Fir post, from which