

## County Surveyor's Record, Douglas County, Oregon

47

## Subdivisions of T. 29 S., R. 4 W.

## CHAINS

- 65.48 Intersect line, 10.50 chs. N. of cor. to Secs. 9, 10,  
3 and 4.  
N.80°53'W., on True line between Sections 4 and 9.
- 32.74 Set a Fir post for the  $\frac{1}{4}$  sec. cor., from which  
A Fir, 15 ins. diam., bears S.28°W., 18 lks. dist.  
An Alder, 12 ins. diam., bears N.45°W., 40 lks.  
dist.
- 38.18 Creek, 2 lks. wide, C. N.75°W.
- 57.48 Creek, 3 lks. wide, C. W.
- 65.48 To Section corner.  
Land, mountainous, heavily timbered, 2nd rate.  
Timber, chiefly Fir, Cedar, Hemlock and Laurel.
- 
- North, on Random line between Sections 4 and 5.  
Var. 19°E.
- 40.00 Set temp.  $\frac{1}{4}$  sec. cor.
- 79.60 Intersect line 10 lks. E. of cor. to Secs. 4, 5, 32 and  
33.  
S.0°04'E., on True line.
- 14.20 Co. Road, C. E. and W.
- 16.50 Creek, 50 lks. wide, C. W.
- 39.60 Set Fir post for  $\frac{1}{4}$  sec. cor., from which  
A Fir, 40 ins. diam., bears S.89°E., 33 lks. dist.  
A Fir, 12 ins. diam., bears N.20°W., 32 lks. dist.
- 65.00 Top of ridge, C. SW.
- 79.60 To Section corner.  
Land, mountainous, 2nd rate.  
Timber, chiefly Fir, Cedar, Oak and Laurel.  
April 11, 1881.

From the corner to Secs. 4, 5, 8 and 9.

West, along old line between Secs. 5 and 8.

Var. 19°E.