

County Surveyor's Record, Douglas County, Oregon

6419

-1-

West Boundary of T. 29 S., R. 5 W., W.M.  
 as surveyed by Deputy Surveyor, Nathaniel Ford, under his  
 Contract No. 44, dated May 30th, 1854.

CHAINS		
	Township line, commence, June 19th, 1854	
	West boundary	
	Va. 18*25'E.	
	South on West boundary of Sec. 6.	
	Began to descend hill	
40.00	Foot of hill. Set quarter section post, from which An Ash, 15 ins. diam., bears S.15*W., 235 lks. dist. An Ash, 12 ins. diam., bears N.67*E., 214 lks. dist.	-200
42.00	A ravine, 20 lks. wide, course S.45*W.	level
45.00	Began to ascend hill	
59.00	Top of ridge bears SW. and NE.	+ 150
63.00	Began to descend hill.	
80.00	Set a post for cor. to secs. 1, 12, 6 and 7, from which, A B. Oak, 8 ins. diam., bears S.55*E., 21 lks. dist. A Laurel, 18 ins. diam., bears N.87*E., 100 lks. dist. A W. Oak, 12 ins. diam., bears N.89*W., 35 lks. dist. A B. Oak, 20 ins. diam., bears S.51*W., 250 lks. dist. Second rate soil. Timber, Oak openings.	-125
	Va. 18*10'E.	
	South on West boundary of Sec. 7.	
35.00	Right bank of S. Umpqua River course S.78*W.	-100
38.00	Left bank of river	+ 20
40.00	Set a 1/4 sec. post, from which A W. Oak, 15 ins. diam., bears S.80*W., 60 lks. dist. A W. Oak, 20 ins. diam., bears N.20*E., 45 lks. dist.	level