

West Boundary of T. 29 S. R. 6 W.
 As surveyed by Nathaniel Ford, Deputy Surveyor,
 under contract No. 44, dated May 30, 1854.

CHAINS		
	Commenced on the line dividing ranges 6 and 7 at the SW. corner of Tp. 28 S R 6 W and run the Exterior lines of Tp. 29 South of the Base line of range 6 West of the Willamette Meridian.	
	Va. 18°20'E.	
	South, on the West Bdy. of sec. 6.	
3.50	Small Stream, 4 lks. wide, course NW.	-20
20.00	Top of Ridge, course SW. and NE.	+10
40.00	Set $\frac{1}{2}$ sec. post, from which:	-100
	A Laurel, 10 ins. diam., bears N.25°W., 450 lks. dist.	
	A B. Oak, 5 ins. diam., bears N.5°E., 425 lks. dist.	
45.20	Small Stream, 4 lks. wide, course NE.	
80.00	Set a post corner of secs. 1, 6, 7 and 12, from which:	
	A Red Fir, 16 ins. diam., bears N.45°W., 29 lks. dist.	
	A Red Fir, 18 ins. diam., bears N.65°E., 70 lks. dist.	
	A Laurel, 8 ins. diam., bears S.50°E., 20 lks. dist.	
	A Laurel, 7 ins. diam., bears S.35°W., 75 lks. dist.	
	Soil: third rate- Timber; oak, pine, fir.-Underbrush; Laurel and oak.	
	Land; hilly.	
	Va. 18 $\frac{1}{2}$ °E.	
	South, on West Bdy. of sec. 7	
5.00	Entered oak openings.	+20
	Top of flat ridge.	
40.00	Set $\frac{1}{2}$ sec. post, from which:	level