

County Surveyor's Record, Douglas County, Oregon

6489

Subdivisions of fractional T. 29 S. R. 6 W.
As surveyed by W. H. Byars, Deputy Surveyor, under
contract No. 152, dated June 3rd. 1871.

CHAINS		
	From the cor. to secs. 3, 4, 33 and 34, on the South Bdy. of Township I run, North, bet. secs. 33 and 34.	
	Va. 29*E.	
40.00	Set $\frac{1}{2}$ sec. post, from which: A Chinquapin, 20 ins. diam., bears N.80*E., 45 lks. dist. A Fir, 30 ins. diam., bears N.30*W., 17 lks. dist.	-100
	Va. 21*E.	
47.50	A Creek, 3 lks. wide, Course NW.	-150
59.50	Top of bluff, 50 ft. high.	
60.00	Foot of same.	
80.00	Set post, cor. to secs. 27, 28, 33 and 34, from which: A Cedar, 20 ins. diam., bears N.50*E., 13 lks. dist. A Maple, 6 ins. diam., bears S.35*E., 33 lks. dist. A Maple, 10 ins. diam., bears S.30*W., 13 lks. dist. A Cedar, 20 ins. diam., bears N.40*W., 37 lks. dist. Post in edge of Creek, 5 lks. wide, Course NW. Land; brushy, second rate. Timber; fir, cedar, laurel, yew and maple, first rate.	
	Va. 20*E.	
40.00	Set temp. sec. post.	
80.00	Could find no post or line. Set temp. post.	