

Subdivisions of a portion of T. 29 S. R. 6 W.

CHAINS

A Laurel, 16 ins. diam., bears S.50*E., 22
lks. dist.

Soil; second rate, covered with fir timber.

North, on random line bet. secs. 28 and 29.

Va. 19*E.

79.58 Intersect cor. to secs. 20, 21, 28 and 29.

Found witness trees, as follows:

A B. Oak, 12 ins. diam., bears S.25*E., 34
lks. dist.

A B. Oak, 14 ins. diam., bears N.35*E., 10
lks. dist.

A B. Oak, 6 ins. diam., bears N.37*W., 35
lks. dist.

A B. Oak, 8 ins. diam., bears S.47*W., 25
lks. dist.

Thence South, on true line bet. secs. 28 and 29.

Va. 19*E.

6.00 Branch bears NE.

39.79 Set $\frac{1}{4}$ sec. post, from which:

An Ash, 8 ins. diam., bears N.90*W., 34
lks. dist.

A Maple, 10 ins. diam., bears S.85*E., 21
lks. dist.

79.58 To Cor.

Soil; poor and hilly.

Subdivision Lines of T. 29 S. R. 6 W.
of the Willamette Meridian, as surveyed by Fred
Mensch, U. S. Deputy Surveyor, under his contract
No. 757, dated September 14, 1904.

At the corner of secs. 19, 20, 29 and 30,

Thence I run

S.0*1'E. bet. secs. 29 and 30.