

Subdivision of T. 29 S. R. 6.W.

CHAINS

From the cor. of secs. 28, 29, 32 and 33, already described, I run

S.0*1'E. on a random line bet. secs. 32 and 33.

40.00 Set temp. 1/4 sec. cor.

81.25 Intersect S. bdy of the Tp. 10.77 chs. S.89*54' E. of the cor. of secs. 4, 5, 32 and 33, which is a post greatly decayed, witnessed as described by the surveyor general.

Set a limestone 15x8x6 ins., 10 ins. in the ground for closing cor of secs. 32 and 33, marked CC on N, with 4 grooves on E. and 2 grooves on W. face, from which:

A white fir, 12 ins. diam., bears N.43*E., 31 lks. dist., marked T 29 S R 6 W S 33 B T

A white fir, 10 ins. diam bears N.83*W., 60 lks. dist., marked T 29 S R 6 W S 32 B T

I destroy marks on former corner and bearing trees referring to these secs.

Thence I run

N.0*1'W. on a true line bet secs. 32 and 33.

Over mountainous land through heavy timber and dense undergrowth.

Desc. NE slope.

12.25 Creek, 2 lks. wide, course NE.

15.75 Creek, 2 lks. wide, course E.

Asc. SE. slope.

24.25 Summit of ridge, bears E. and W.

Desc. NE. slope.

32.25 Creek, 1 lk. wide, course E.

41.25 Set an ironstone, 14 x 10 x 6 ins. 9 1/2 ins. in the ground for 1/4 sec. cor. marked 1/4 on W. face, from which:

A red fir, 7 ins. diam., bears S.60*E., 56 lks. dist., marked 1/4 S 33 B T

A red fir, 6 ins. diam., bears N.63*W., 33 lks. dist., marked 1/4 S 32 B T