

Re-Survey of Portions of the West and South Bdys.  
of T. 29 S., R. N. 6 W., of the Willamette Meridian,  
as surveyed by Fred Mensch, U. S. Deputy Surveyor, under  
contract No. 757, dated September 14, 1904.

CHAINS

I hereby affirm that the re-surveys and retracements of the West and South boundaries of T. 29 S., R 6 W, described in the following field notes, were absolutely necessary in connection with the survey of the lines completing the subdivision of secs 29, 30, 31, 32 and 33.

The West boundary of secs. 30 and 31 was run primarily to re-establish the obliterated corner of secs. 25, 30 31 and 36, and its retracement is also necessary to account for the excessive closure of the lines bet secs. 31 and 32 and bet secs 32 and 33.

The South boundary of secs 31 and 32 was run to account for closing distances out of limits with reported lengths and bearings.

Fred Mensch

U.S. Deputy Surveyor.

Re-Survey of West Boundary of T. 29 S., R 6 W.

I commence at the cor. of Tps. 29 and 30 S Rs. 6 and 7 W, which I find partially obliterated. The oaks described, as bearing trees in secs. 1 and 31 are standing, with marks yet distinguishable. The other bearing trees have disappeared. I destroy the old marks and re-establish the corner in its original position, as follows:

Set a diorite stone 15x12x10 ins. 10 ins. in the ground for cor of Tps 29 and 30 South, Rs 6 and 7 W, marked with 6 notches on each edge, from which:

A White Oak, 24 ins. diam., bears N.73°E., 22 lks. dist., marked T 29 S R 6 W S 31 B T

A White Oak, 18 ins. diam., bears S.20°E., 50 lks. dist., marked T 30 S R 6 W S 6 B T

A Yellow Pine, 36 ins. diam., bears S.19°W., 46 lks. dist., marked T 30 S R 7 W S 1 B T