

## Re-Survey of W. bdy of T. 29 S., R. 6 W.

## CHAINS

A Cedar, 12 ins. diam., bears N.49\*W., 150  
lks. dist., marked T 29 S R 7 W S 36 B T

Thence I run

North, on a random line bet secs. 31 and 36.

40.00 The 1/4 sec. cor. is not found after careful search.

Set temp. 1/4 sec. cor.

80.00 At this point I again make careful search for the cor

of secs. 25, 30, 31 and 36, but find no traces of  
post or bearing trees. Set temp. sec. cor.

Thence North bet secs. 25 and 30.

80.19 The temp sec cor set at termination of random line bet

sec. 30 and 31 bears East 350 lks. dist.

120.00 The 1/4 sec. cor. bet secs. 25 and 30 is not found after

careful search. Set temp. 1/4 sec. cor.

158.80 Intersect E. and W. line 692 lks. West of the cor of

secs. 19, 24, 25 and 30.

This corner has evidently been restored at a later date  
than that of the original survey. I find, however,  
one of the original bearing trees still standing and  
re-establish the cor in its original position as  
follows: destroying former cor and marks on bearing  
trees:

Set a sandstone 16x10x4 ins. 11 ins. in the ground  
for cor. of secs. 19, 24, 25 and 30, marked with 4  
notches on N. and 2 notches on S. edge, from which:

A Maple, 18 ins. diam., bears N.53\*E., 11  
lks. dist., marked T 29 S R 6 W S 19 B T

A Maple, 14 ins. diam., bears S.75\*E., 18  
lks. dist., marked T 29 S R 6 W S 30 B T

A Maple, 12 ins. diam., bears S.3\*W., 14  
lks. dist., marked T 29 S R 7 W S 25 B T