

County Surveyor's Record, Douglas County, Oregon

Re-Survey of S. Bdy. of T. 29 S. R. 6 W.

CHAINS
38.94

The $\frac{1}{4}$ sec. cor., which is a post greatly decayed, witnessed, as described by the surveyor general, bears South 21 lks. dist.

The course of this line is S.89°36'E. and the length is 38.94 chs.

Commencing at the $\frac{1}{4}$ sec. cor. I run S.89°54'E. bet. secs. 5 and 32.

2.21 Gulch, course SW.

8.20 Leave heavy timber, bears NW. and SE.

Enter grassy opening on S. slope of mountain.

13.71 Summit of divide bet. Olalla and Willis creeks bears NW. and SE.

Descend NE. slope.

24.20 Enter heavy timber, bears N. and S.

39.21 The cor. of secs. 4 and 5, which is a post greatly decayed, witnessed as described by the surveyor general, bears S. 42 lks. dist.

The course of this line is S.89°18'E. and the length is 39.21 chs.

Land, mountainous.

Soil, clay and stony, 2nd and 3rd rate.

Timber, red and white fir, sugar pine and cedar.

Undergrowth, fir, oak, arrowwood and hazel.

Mountainous or heavily timbered land or land covered with dense undergrowth, 78.15 chs.

July 31, 1905.

Re-Establishment of Corners in T. 29 S. R. 6 W.

December 4, 1905.

The $\frac{1}{4}$ sec. cor. bet. secs. 6 and 31, on the South bdy. of T. 29 S R 6 W., being partially obliterated, I re-establish this corner in its original position, as follows:

Set a basalt stone 18x14x10 ins. 12 ins. in the ground for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ on N. face; from which