

Re-Establishment of Corners in T. 29 S., R. 6 W.

CHAINS

December 5, 1905. The $\frac{1}{4}$ Sec. corner bet. Secs. 20 and 29 being nearly obliterated, I re-establish this corner in its original position, as follows:

Set a Porphyry stone, 15x10x6 ins., 10 ins. in the ground, for $\frac{1}{4}$ Sec. corner marked $\frac{1}{4}$ on N face, from which

A Red Fir, 14 ins. diam., bears N.28*W., 15 lks. dist., marked $\frac{1}{4}$ S 20 B T.

A Black Oak, 12 ins. diam., bears S.40*W., 10 lks. dist., marked $\frac{1}{4}$ S 29 B T.

December 5, 1905.

Retracement of the E Bdy. of T. 29 S., R. 7 W. of the Willamette Meridian, as surveyed by Roy T. Campbell, U. S. Deputy Surveyor, under his contract #789, dated August 21, 1909.

At the corner of Tps. 29 and 30 S., Rgs. 6 and 7 W.

Thence I run

N.2*30'E., on a retracement, bet. Secs. 31 and 36.

Ascend S slope, through heavy timber and scattering undergrowth.

31.00 Summit of divide, bet. Rice and Olalla Creeks, bears E and W., 300 ft., above Sec. corner. Thence descend.

38.67 Intersect the old $\frac{1}{4}$ Sec. cor., which is a post, 4 ins. sq., 12 ins. above ground, firmly set, marked and witnessed as described by the Surveyor General.

Therefore this line, S. of the $\frac{1}{4}$ Sec. corner, is 38.67 chs. in length, and bears N.2*30'E.

I continue the retracement from the $\frac{1}{4}$ Sec. corner.

78.59 At a point 250 ft. below top of divide, intersect the corner of Secs. 25, 30, 31 and 36, which is a post, 4 ins. sq., 12 ins. above ground, firmly set, marked and witnessed as described by the Surveyor General.