

Resurvey of the North Bdy. of T. 30 S., R. 7 W.  
As surveyed by William H. Byars, Deputy Surveyor,  
Under Contract No. 456, dated July 28, 1882.

CHAINS

Being unable to find the North boundary of Township 30 South, R. 7 W., or any traces thereof West of the corner to secs. 2, 3, 34 and 35; therefore, I proceed to re-establish the same.

From the established corner to Township 29, South Ranges 7 and 8 West, the corner heretofore described.

Thence, I run, East, on a Random line, between Townships 29 and 30 S., R. 7 W.

Va. 19°E.

I set temporary half-mile and mile corners at each 40 and 80 chains, and at 4 miles 1 chain and 63 lks., I intersect a point 11.28 lks. due S. of the established corner to secs. 2, 3, 34 and 35, which is a post, 4 ins. square, firmly set in the ground and marked T. 29 S., S35 on NE. face, and R 7 W S 2 on the S<sup>w</sup>. face, T 30 S S 3 on the SW. face and S 34 on the NW. face; also, 2 notches on the East angles, and 4 notches on the West, and from which,

A Laurel, 5 ins. diam., bears N.40°E., 8 lks. dist.

Marked T.29 S R 7 W S 35 B T.

A Laurel, 6 ins. diam., bears S.75°E., 6 lks. dist.

Marked T 30 S R 7 W S 2 B T.

A Laurel, 6 ins. diam., bears S.10°W., 18 lks. dist.

Marked T 30 S R 7 W S 3 B T.

A Laurel, 8 ins. diam., bears N.60°W., 17 lks. dist.

Marked T 29 S R 7 W S 34 B T.

The correction for the true line will therefore be 2.82 chs. South and 163 lks. East per mile, and the course will be S.87°59'W.

September 20 and 21, 1882.