

County Surveyor's Record, Douglas County, Oregon

Resurvey of the North Bdy. of T. 30 S., R. 7 W.

CHAINS

S.87*59'W., on true line between secs. 3 and 34.

Va. 19*30'E.

- 8.00 Moderate ascent.
- 17.00 Pine opening.
- 20.00 Top of spur, Course S.
Moderate descent.
- 40.00 Set a Fir post, 4 feet long, 4 ins. square, 20 ins. in ground, for the $\frac{1}{4}$ sec. corner, marked $\frac{1}{4}$ S. on the N. face, from which,
A Fir, 18 ins. diam., bears S.20*E., 19 lks. dist.
Marked $\frac{1}{4}$ S. B T.
A Pine, 18 ins. diam., bears N.48*W., 122 lks. dist.
Marked $\frac{1}{4}$ S. B T.
- 44.00 Foot of hill.
- 48.00 Begin ascent.
- 67.00 Top of spur, Course S.
Descend.
- 80.00 Set a Pine post, 4 $\frac{1}{2}$ feet long, 4 ins. square, 24 ins. in ground for the corner to secs. 3, 4, 33, and 34, marked T 29 S R 7 W S 34 on the NE. face, T 30 S S 3 on SE. face, S 4 on the SW. face and S 33 on the NW. face; also, 3 notches on the East and 3 notches on the West angles of the same, and from which,
A Pine, 36 ins. diam., bears N.74*E., 152 lks. dist.
Marked T 29 S R 7 W S 34 B T.
A Pine, 4 ins. diam., bears S.25*E., 15 lks. dist.
Marked T 30 S R 7 W S 3 B T.
A Pine, 6 ins. diam., bears S.75*W., 5 lks. dist.
Marked T 30 S R 7 W S 4 B T.
A Pine, 6 ins. diam., bears N.30*W., 16 lks. dist.
Marked T 29 S R 7 W S 33 B T.
- Land, mountainous and hilly.
Soil, second and third rates.