

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 29 S., R. 7 W.,
Same Deputy and Contract.

CHAINS

Note: The exterior lines of the Township being defective in alinement and measurement I proceed to establish a sectional correction line and sectional guide meridian. From the corner of secs. 1, 2, 35 and 36, and 25, 30, 31 and 36 I extend lines due North and West, respectively, to their mutual intersection, where I establish the corner of secs. 25, 26, 35 and 36. From this corner I establish sectional correction line due West, and sectional guide meridian, due North.

From the corner of secs. 1, 2, 35 and 36.

I run

North on a random line bet. secs. 35 and 36.

40.00 Set temporary $\frac{1}{2}$ sec. corner.

80.00 Set temporary corner for corner of secs. 25, 26, 35 and 36.

June, 30, 1910.

July 1, 1910: At 8h 3m A.m., l.m.t., I set off 43*1' North on the latitude arc, 23*10' North on the declination arc, and determine a meridian with the solar at the corner of secs. 25, 30,,31 and 36, on the East boundary.

Thence I run

W. on a random line between secs. 25 and 36.

40.00 Set temporary $\frac{1}{2}$ sec. corner.

84.49 Intersect N. and S. random line, 2.44 chs. S. of the temporary corner of secs. 25, 26, 35 and 36.

At the point of intersection

I set a granite stone, 15 x 12 x 4 ins., 10 ins. in the ground for corner of secs. 25, 26, 35 and 36, marked with 1 notch in S. and E. edges, from which,