

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 29 S., R. 7 W.

CHAINS

of secs. 26, 27, 34 and 35, which is in a bad state of preservation. I re-establish it at the same point for corner of secs. 27 and 34 only, as follows:

Set a conglomerate stone, 15 x 12 x 10 ins., 10 ins. in the ground, for corner of secs. 27 and 34, marked with 1 notch on S. and 2 notches on E. edge, from which,

A Fir, 18 ins. diam., bears S.22*30'W., 24 lks. dist.

Marked T 29 S R 7 W S 34 B T.

A Fir, 12 ins. diam., bears N.2*30'W., 47 lks. dist.

Marked T 29 S R 7 W S 27 B T.

At the point of intersection with N. and S. line,

I set a conglomerate stone, 18 x 12 x 10 ins. 12 ins. in the ground, for C. C. for secs. 26 and 35, marked C. C. on E., with 1 groove on S. and 2 grooves on E. face, from which,

A Fir, 30 ins. diam., bears N.12*45'E., 45 lks. dist.

Marked T 29 S R 7 W S 26 B T.

A Fir, 30 ins. diam., bears S.31*45'E., 40 lks. dist.

Marked T 29 S R 7 W S 35 B T.

Land, mountainous.

Soil, stony, second and 3rd rate.

Timber, Fir, Cedar, Maple, Madrona, Pine and Myrtle.

Undergrowth, Chinquapin and Willow.

July 2, 1910: Note: Sky overcast at noon, observation for latitude impossible.

July 2, 1910.

July 3, 1910: At 8h 4 M a.m., 1.m.5., I set off 43*1' North on the latitude arc, 23*1' North on the declination arc, and determine a meridian with the solar at the corner of secs. 25, 26, 35 and 36.