

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 29 S., R. 7 W.

CHAINS.

A Fir, 12 ins. diam., bears N.59°30'E., 47 lks. dist.

Marked $\frac{1}{2}$ S 24 B. T.

A Fir, 14 ins. diam., bears S.67°45'W., 6 lks. dist.

Marked $\frac{1}{2}$ S 25 B T.

July 4, 1910: At this corner I set off 22°56' North on the declination arc, and at 12h 4m l.m.t., observe the sun on the meridian; the resulting latitude is 43°2'.

88.11 At a point 150 ft. below top of ridge.

Intersect E. bdy. of Tp., 1.58 chs. N. of the cor. of secs. 19, 24, 25 and 30, which is a post, 4 ins. square 12 ins. above ground, firmly set, marked and witnessed as described by the Surveyor General.

At the point of intersection with the E. bdy. of Tp.

I set a conglomerate stone, 15 x 12 x 8 ins., 10 ins. in the ground, for C. C. for secs. 24 and 25, marked C. C. on the W., with 2 grooves on S. and 4 grooves on N. face, from which,

An Ash, 18 ins. diam., bears S.55°45'W., 293 lks. dist.

Marked T 29 S R 7 W S 25 B T.

A Fir, 24 ins. diam., bears N.82°W., 161 lks. dist.

Marked T 29 S R 7 W S 24 B T.

Land, mountainous.

Soil, stony, second and third rate.

Timber, Fir, Cedar, Madrona, Pine, Oak and Ash.

Undergrowth, Maple, Chinquapin and Willow.

July 4, 1910.

The corner of secs. 23, 24, 25 and 26.

Thence I run

W. on a true line between sec. 23 and 26.

Descend W. slope, over mountainous land, through heavy