

## Retracement of Subdivisional Lines of Fractional T. 29 S., R. 9 W.,

CHAINS

Mountainous land, or land heavily timbered or covered with dense undergrowth and exceptionally difficult to survey 80.80 chains.

June 28, 1907.

Subdivisional Lines of Fractional T. 29 S., R. W.,  
of the W M., Oregon,  
As surveyed by William M Porter, Deputy Surveyor,  
Under contract N. 768, Dated March 8, 1907.

At the cor. of secs 21-22-27 and 28, cor. described in my notes under this survey.

Thence I run

N.0\*1'W. between secs. 21 and 22 over mountainous land, heavily timbered.

.80 A creek, 6 lks. wide; C. E. Ascend through heavy timber and dense undergrowth.

8.75 Rocky bluff 20 ft. high, C. N.E. and S.W.

11.75 Top of ridge, C.E. and W. about 300 ft. elevation.  
Steep descent.

29.00 A creek, 4 lks. wide; C. N.E. about 300 ft. lower elevation.

Water-fall and canyon 75 ft. deep;

Offset W., 75 lks. thence N., 2.50 chs., thence E., 75 lks. to line.

31.50 Resume line.

37.25 A creek, 3 lks. wide; C. S.E.

Steep ascent.

40.00 Set a basalt stone 11x11x8 ins., 8 ins., in ground marked  $\frac{1}{4}$  on W. face, from which

A hemlock 10 ins. in diam. bears S.87\*E., 50 lks.

Marked  $\frac{1}{4}$  S 22 B T

A hemlock 15 ins. in diam. bears N.87\*W., 40 lks.

Marked  $\frac{1}{4}$  S 21 B T

56.00 Rocky bluff 30 ft. down, C. N. & S.

Offset to W., 50 lks., thence N. 5 chs.

A creek, 1 lk. wide, C.E. at 4 chs.

61.00 E., 50 lks. to line.