

WILLAMETTE MERIDIAN  
Through T. 30 S.As surveyed by Homer D. Angell, Deputy Surveyor  
Under contract No. 746, dated May 5, 1902.

## CHAINS

Willamette Meridian, through T. 30 S.,

From the corner of Ts. 30 and 31 S., I run

North, bet. secs. 31 and 36.

- 1.33 A fir, 30 ins. diam., on line I mark with two notches on N. and S. sides.
- 35.00 A spring branch, 1 lk., C. SW.
- 38.00 A fir, 24 ins. diam., on line I mark with two notches on N. and S. sides. Difference between measurement of 40.00 chs. by two sets of chainmen is 14 lks., position of middle point.
- By 1st set, 40.07
- By 2nd set, 39.93
- the mean of which is
- 40.00 Set a basalt stone 15x12x6 ins., 10 ins. in ground for  $\frac{1}{4}$  sec. corner, marked  $\frac{1}{4}$  on W. face; from which
- A fir, 30 ins. diam., bears N.29\*E., 22 lks. dist., marked  $\frac{1}{4}$  S 31 B T.
- A fir, 20 ins. diam., bears S.75\*W., 14 lks. dist., marked  $\frac{1}{4}$  S 36 B T.
- 54.00 Top of divide, 1500 ft. high., bears S.60\*E., N.60\*W.
- 58.15 Mountain trail, bears E. and W. Difference between measurement of 80.00 chs. by two sets of chainmen is 8 lks. position of middle point.
- By 1st set, 80.04
- By 2nd set, 79.96
- the mean of which is
- 80.00 Set a basalt stone, 20x10x8 ins., 15 ins. in ground for corner of secs. 25 and 36, marked with 5 notches on N. and 1 notch on S. edges, from which
- A fir, 18 ins. diam., bears S.64\*W., 32 lks. dist., marked T 30 S R 1 W S 36 B T.
- A fir, 18 ins. diam., bears N.10\*W., 42 lks. dist., marked T 30 S R 1 W S 25 B T.
- Land, mountainous.