

Willamette Meridian
Through T. 30 S.

CHAINS

A fir, 12 ins. diam., bears S.64*W., 30 lks. dist.,
marked T 30 S R 1 W S 24 B T.

A fir, 30 ins. diam., bears N.50*W., 38 lks. dist.,
marked T 30 S R 1 W S 13 B T.

From this corner the old sec. corner for secs. 13, 18,
19 and 24 bears N.83*7'W., 29.60 chs. dist. The stake
is completely decayed but is witnessed as described by
the surveyor general. In the place of the stake at the
original point, I set

A basalt stone, 20x14x10 ins., 15 ins. in the ground
for corner of secs. 13 and 24, marked with 3 notches
on N. and S. edges. I destroy all marks on the corner
referring to T. 30 S., R. 1 E.

Land, mountainous.

Soil, stoney and third rate.

Timber, fir, pine, cedar, and hemlock.

Undergrowth, laurel and willow.

Mountainous or heavily timbered land or land covered
with dense undergrowth, 80.00 chs.

North, bet. secs. 13 and 18.

Ascend through heavy timber and dense undergrowth.

6.50 South fork of Umpqua River, 75 lks. wide, C. W.

7.50 Ascend, bears E. and W.

31.50 Top of ridge point, bears SE. and NW., desc.

Difference bet. measurement of 40.00 chs. by two set
of chainmen is 14 lks.; position of middle point

By 1st set, 40.07

By 2nd set, 39.93

the mean of which is

40.00 Set a basalt stone 14x10x6 ins., 10 ins. in ground
for $\frac{1}{4}$ sec. corner, marked $\frac{1}{4}$ on W. face, from which