

Willamette Meridian
Through T. 30 S.

CHAINS

- A fir, 30 ins. diam., bears N.35*E., 15 lks. dist., marked $\frac{1}{4}$ S 18 B T.
- A fir, 30 ins. diam., bears S.3*W., 46 lks. dist., marked $\frac{1}{4}$ S 13 B T.
- 40.80 A fir, 60 ins. diam., on line I mark with two notches on N. and S. sides.
- 42.00 A spring branch, 10 lks. wide, C. E.; asc.
Difference between measurement of 80.00 chs. by two sets of chainmen is 8 lks.; position of middle point
By 1st set, 80.04
By 2nd set, 79.96
the mean of which is
- 80.00 Set a basalt stone, 15x12x12 ins., 10 ins. in ground for corner of secs. 12 and 13, marked with 2 notches on N. and 4 notches on S. edges, from which
A fir, 12 ins. diam., bears S.13*W., 106 lks. dist., marked T 30 S R 1 W S 13 B T.
A pine, 20 ins. diam., bears N.48*W., 11 lks. dist., marked T 30 S R 1 W S 12 B T.
From this corner the old corner of secs. 7, 12, 13 and 18 which is a post marked and witnessed as described by the surveyor general, bears N.81*20' W. 29.79 chs. dist., I destroy all marks on this corner referring to T. 30 S., R. 1 E.
Land, mountainous.
Soil, stoney and third rate.
Timber, fir, pine and hemlock.
Undergrowth, laurel and huckleberry.
Mountainous or heavily timbered land or land covered with dense undergrowth, 80.00 chs.
-
- North, bet. secs. 7 and 12.
Over W. slope through heavy timber and scattering undergrowth.