

Supplemental Notes of T. 30 S., R. 1 W.
Same Deputy and Contract.

CHAINS

Retracement of line E. from the $\frac{1}{4}$ sec. corner bet. secs. 5 and 8 to $\frac{1}{4}$ sec. corner bet. secs. 4 and 9 indicates that the corner of secs. 4 and 5 should be placed at a point 15 lks. N. of its former position and I so re-establish this corner as follows:

Set a basalt stone 15x8x6 ins. 10 ins. in the ground for corner of secs. 4 and 5, marked with 4 notches on E. edge; from which

A fir, 18 ins. diam., bears N.78*E., 64 lks. dist., marked T 30 S R 1 W S 4 B T.

A yew, 14 ins. diam., bears N.13*W., 50 lks. dist., marked T 30 S R 1 W S 5 B T.

Retracement of line N. from the $\frac{1}{4}$ sec. corner bet. secs. 8 and 9 indicates that the corner of these secs. on sectional correction line should be placed 5 lks. E. To conform with examiners report of the bearing of the former corners and with the new position of the corners of secs. 4 and 5, it should be placed 21 lks. N. of its former position and I so establish this corner as follows:

Set an ironstone 20x12x8 ins., 15 ins. in the ground for closing corner of secs. 8 and 9, marked C C on S. with 4 grooves on E. and 5 grooves on S. faces; from which

A white fir, 10 ins. diam., bears S.11*E., 37 lks. dist., marked T 30 S R 1 W S 9 B T.

A white fir, 10 ins. diam., bears S.2*W., 82 lks. dist., marked T 30 S R 1 W S 8 B T.

I destroy former corners of secs. 4 and 5 and 8 and 9 and marks on bearing trees not used for new corners.

Thence, I run

North, on a random line bet. secs. 4 and 5.

40.00 Set temp. $\frac{1}{4}$ sec. corner.

81.02 Intersect N. bdy. of Tp., 18 lks. W. of the corner of secs. 4, 5, 32 and 33, which I established November 10, 1907.