

County Surveyor's Record, Douglas County, Oregon

Supplemental Notes of T. 30 S., R. 1 W.

CHAINS	
	Thence, I run
	S. 0° 8' W. on a true line bet. secs. 4 and 5.
	Over mountainous land, through scattering timber and dense undergrowth.
	Descend S. slope.
5.60	Creek, 5 lks. wide, C. S. 20° E.
8.00	Creek, 3 lks. wide, C. SE.
13.80	Ravine, C. SE. Ascend NE. slope.
16.00	Summit of ridge, bears NW. and SE.
	Descend SW. slope.
28.10	North fork of South Umpqua River, 75 lks. wide, C. SW.
	Ascend NW. slope.
41.02	Set a basalt stone 14x8x6 ins., 10 ins. in the ground for $\frac{1}{4}$ sec. corner, marked $\frac{1}{4}$ on W. face; from which:
	A fir, 30 ins. diam., bears S. 18° E., 23 lks. dist., marked $\frac{1}{4}$ S 4 B T.
	A fir, 48 ins. diam., bears N. 88° W., 12 lks. dist., marked $\frac{1}{4}$ S 5 B T.
41.37	The corner which I established under contract NO. 757 as the $\frac{1}{4}$ sec. corner bet. secs. 4 and 5 bears E. 10 lks. distance. I destroy the corner and marks on bearing trees.
77.35	Creek, 3 lks. wide, C. NW.
81.02	The corner of secs. 4 and 5 on sectional correction line.
	Land, mountainous.
	Soil, clay, loam and stony. Second and third rate.
	Timber, red and white fir, sugar and yellow pine, cedar.
	Undergrowth, arrowwood, hazel and vine maple.
	Mountainous or heavily timbered land or land covered with dense undergrowth, 81.02 chains.