

6691^A County Surveyor's Record, Douglas County, Oregon

Subdivision of T. 30 S., R. 1 W.

| | |
|--------|--|
| CHAINS | <p>Distance from $\frac{1}{4}$ sec. corner of S. bdy. of sec. 5 to corner of secs. 4 and 5, 40.00 chas. Distance from corner of secs. 4 and 5 to $\frac{1}{4}$ sec. corner on S. bdy. sec. 4, 40.00 chains. Distance from $\frac{1}{4}$ sec. corner bet. secs. 8 and 9 to C. C. of secs 8 and 9 is 42.00 chs.</p> |
| | <p>Subd. of T. 30 S., R. 1 W., Resurveyed by Fred Mensch in 1905.</p> |
| | <p>The Witness Corner reported set at 33.40 chs. E. of the corner of secs. 5, 6, 7 and 8, is not found after careful search. I commence, therefore, at the cor. of secs. 5, 6, 7 and 8, which is nearly obliterated. The old corner which was a post has disappeared and only indistinct remains of the mound of stone are found. The oak described as a bearing tree in sec. 7 is still standing with marks yet distinguishable. The other bearing trees have fallen and decayed.</p> <p>I destroy the old marks and reestablish the corner in its original position, as follows:</p> <p>Set a basalt stone, 18x10x8 ins. 12 ins. in the ground, for corner of secs. 5, 6, 7 and 8, marked with 5 notches on S. and E. edges, from which:</p> <p style="padding-left: 40px;">A red fir, 15 ins. diam., bears N. 65° E. 18 lks. dist. marked T30S., R 1 W, S 5 B T.</p> <p style="padding-left: 40px;">A red fir, 18 ins. diam., bears S. 68° E. 89 lks. dist., marked T 30 S, R 1 W, S 8 B T.</p> <p style="padding-left: 40px;">A red fir, 10 ins. diam., bears S. 70° W. 44 lks. dist., marked T 30 S, R 1 W, S 7 B T.</p> <p style="padding-left: 40px;">A red fir, 8 ins. diam., bears N. 10° W. 46 lks. dist., marked T 30 S, R 1 W, S 6 B T.</p> <p>Thence I run</p> <p>East on a true line bet. secs. 5 and 8.</p> <p>Over mountainous land through dense undergrowth.</p> <p>Descend S.E. slope.</p> <p>3.64 Settlers' trail from Tiller bears N. and S.</p> <p>32.24 North Fork of South Umpqua River, 80 lks.wide, course SW.</p> <p>Ascend N.W. slope.</p> <p>33.50 Enter heavy timber, bears NE and SW.</p> <p>40.00 Set a basalt stone, 12x10x6 ins. 8 ins. in the ground, $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ on N. face, from which:</p> <p style="padding-left: 40px;">A red fir, 7 ins. diam., bears N. 18° E. 47 lks. dist., marked $\frac{1}{4}$ S 5 BT.</p> <p style="padding-left: 40px;">A red fir, 40 ins. diam., bears S. 80° W., 10 lks. dist., marked $\frac{1}{4}$ S 8 BT.</p> <p>58.00 Summit of ridge bears N. and S.</p> <p>74.25 Gulch, course NW, water in holes.</p> |