

Resurvey of Subdivision, T. 30 S., R. 1 W.

CHAINS

though still standing. I obliterate the old marks and re-establish the corner in its original position as follows:

Set a basalt stone 15x10x8 ins., 10 ins. in the ground for corner of secs. 8, 9, 16 and 17, marked with 4 notches on S. and E. edges; from which

A black oak, 12 ins. diam., bears N.45*E., 131 lks. dist., marked T 30 S R 1 W S 9 B T.

A black oak, 10 ins. diam., bears S.60*E., 68 lks. dist., marked T 30 S R 1 W S 16 B T.

A yellow pine, 24 ins. diam., bears S.82*W., 14 lks. dist., marked T 30 S R 1 W S 17 B T.

A yellow pine, 24 ins. diam., bears N.54*W., 155 lks. dist., marked T 30 S R 1 W S 8 B T.

At the cor. of secs. 8, 9, 16 and 17, I run N.89*28'W. on a true line bet. secs. 8 and 17.

Over mountainous land through dense undergrowth. Along S. slope.

5.00 Enter heavy timber, bears NE. and SW.

40.55 Set an ironstone 14x9x5 ins., 9½ ins. in the ground for ¼ sec. corner, marked ¼ on N. face; from which

A red fir, 24 ins. diam., bears N.74*E., 29 lks. dist., marked ¼ S 8 B T.

A red fir, 20 ins. diam., bears S.40*W., 57 lks. dist., marked ¼ S 17 B T.

45.00 Summit of divide bet. North and South Forks of South Umpqua river, bears NE. and SW.

47.50 Begin descent of steep W. slope.

50.25 Foot of steep descent.

Ascend gradually along NE. slope.

60.00 Summit of ridge bears NW. and SE.

Descend along NW. slope.

81.10 The corner of secs. 7, 8, 17 and 18.

Land, mountainous.