

Resurvey of Subdivisions, T. 30 S., R. 1 W.

CHAINS

Commencing at the $\frac{1}{4}$ sec. corner, I run
 N.89*43'E. bet. secs. 9 and 16.

11.75 Summit of ridge bears N. and S.
 Desc. SE. slope.

13.55 Gulch, C. S.
 Asc. SW. slope.

17.85 Leave scattering timber, bears NW. and SE.
 Enter opening on S. slope of mountain.

19.75 Summit of ridge bears NW. and SE.
 Thence along S. slope.

25.87 Small spring bears N.20 lks. dist.,

29.45 Gulch, C. SW.
 Asc. W. slope.
 Enter scattering timber and dense undergrowth.

40.60 The corner of secs. 9, 10, 15 and 16 bears N. 30 lks.
 dist.
 This corner is partly obliterated. The post is greatly
 decayed and marks on bearing trees are deeply over-
 grown. I re-establish the corner in its original
 position as follows, destroying the old marks.
 Set a basalt stone 24 xl2x8 ins. in mound of stone for
 corner of secs. 9, 10, 15 and 16, marked with 4 notches
 on S. and 3 notches on E. edge; from which

A black oak, 30 ins. diam., bears N.56*E., 100 lks.
 dist., marked T 30 S R 1 W S 10 B T.

A red fir, 7 ins. diam., bears S.8*E., 32 lks.
 dist., marked T. 30 S R 1 W S 15 B T.

A black oak, 18 ins. diam., bears S.23*W., 53 lks.
 dist., marked T 30 S R 1 W S 16 B T.

A black oak, 20 ins. diam., bears N.63*W., 70 lks.
 marked T 30 S R 1 W S 9 B T.