

County Surveyor's Record, Douglas County, Oregon

6701
53



Resurvey of Subdivisions, T. 30 S., R. 1 W.

CHAINS

A red fir, 30 ins. diam., for $\frac{1}{4}$ sec. corner, I mark $\frac{1}{4}$ S 6 on W. and 5 on E. side; from which

A white fir, 14 ins. diam., bears N.54*E., 36 lks. dist., marked $\frac{1}{4}$ S 5 B T.

A white fir, 18 ins. diam., bears N.80*W., 24 lks. dist., marked $\frac{1}{4}$ S 6 B T.

The course of this line is N.0*4'W. and the length is 40.75 chs.

Commencing at the $\frac{1}{4}$ sec. corner, I run N.0*4'W. bet. secs. 5 and 6.

21.73 Settlers' trail bears NW. and SE.

28.46 Creek, 2 lks. wide, C. E.

37.75 Creek, 4 lks. wide, C. SE.

39.75 Intersect corner of secs. 5, 6, 31 and 32, on the N. bdy. of the Tp., which I re-established August 6, 1905.

The C. of this line is N.0*4'W. and the length is 39.75 chs.

Land, mountainous.

Soil, clay, loam and stony, second and third rate.

Timber, red and white fir, sugar pine, cedar, oak and laurel; undergrowth, fir, oak, arrowwood and hazel.

Mountainous or heavily timbered land or land covered with dense undergrowth, 80.50 chs.

Resurvey of East Boundary of T. 30 S., R. 2 W.
As surveyed by Fred Mensch, Deputy Surveyor
Under contract No. 782, dated December 1, 1908.

At the corner of secs. 7, 12, 13 and 18, on the E. bdy. of T. 30 S., R. 2 W.,

I re-establish this corner in its original position as follows:

Set a porphyry stone 18x10x5 ins., 12 ins. in the ground