

County Surveyor's Record, Douglas County, Oregon

6703

Resurvey of East Bdy., T. 30 S., R. 2 W.

CHAINS

Thence, N.0*15'E. on E. bdy. of Sec. 12.

Asc. steep S. slope.

48.00 Summit of steep ascent on end of ridge, bears N.

Thence along ridge.

80.00 Set a conglomerate stone 12x12x10 ins., 8 ins. in the ground for corner of secs. 1 and 12, marked with 1 notch on N. and 5 notches on S. edge, from which

A fir, 18 ins. diam., bears S.24*W., 30 lks. dist., marked T 30 S R 2 W S 12 B T.

A fir, 10 ins. diam., bears N.55*W., 38 lks. dist., marked T 30 S R 2 W S 1 B T.

Land, mountainous.

Soil, clay and stony; second and third rate.

Timber, fir, oak, pine, cedar; undergrowth, hazel, oak and madrona.

Mountainous or heavily timbered land or land covered with dense undergrowth and exceptionally difficult to survey, 80.00 chs.

N.0*15'E. on E. bdy. sec. 1.

Over mountainous land, heavily timbered and covered with dense undergrowth.

Along E. slope.

0.77 In its original position, I re-establish the old corner of secs. 1, 6, 7 and 12 as the corner of secs. 6 and 7, T. 30 S., R. 1 W., only, as follows

Set a basalt stone 12x9x6 ins., 8 ins. in the ground for corner of secs. 6 and 7, marked with 1 notch on N. and 5 notches on S. edge, from which

A fir, 36 ins. diam., bears N.2*E., 82 lks. dist., marked T 30 S R 1 W S 6 B T.

A fir, 30 ins. diam., bears S.80*E., 100 lks. dist., marked T 30 S R 1 W S 7 B T.