

County Surveyor's Record, Douglas County, Oregon

6795

Retracement of Portion of South Boundary of T. 30 S., R. 1 W.  
As surveyed by Fred Mensch, U. S. Cadastral Engineer  
Under Special Instructions, dated June 7, 1922.

CHAINS

From the corner of secs. 4, 5, 32 and 33.  
East, retracing bet. secs. 4 and 33.

40.96 Intersect the old  $\frac{1}{4}$  sec. corner.

81.29 Fall 30 lks. N. of the old corner of secs. 3, 4, 33 and 34.

The bearing and length of the west half mile is East, 40.96 chs., and of the east half mile is S.89\*34'E., 40.33 chs.

Thence  
East, from the sec. corner, bet. secs. 3 and 34.

40.52 Intersect the old  $\frac{1}{4}$  sec. corner.

80.93 Intersect the old corner of secs. 2, 3, 34 and 35.

The bearing and length of the west half mile is E. 40.52 chs., and of the east half mile is E. 40.41 chs.

Thence  
East, from the sec. corner, bet. secs. 2 and 35.

40.17 Fall 26 lks. S. of the old  $\frac{1}{4}$  sec. corner.

80.18 Fall 38 lks. S. of the old cor. of secs. 1, 2, 35 and 36.

The bearing and length of the W. half mile is N.89\*38'E., 40.17 chs., and of the E. half mile is N.89\*50'E., 40.01 chs.

Dependent Resurvey of Portion of S. Bdy., T.30 S., R. 1 W.  
Same Deputy and Contract Number.

The corner of secs. 4, 5, 32 and 33, located by reference to the original bearing trees. From corner point

A laurel, 12 ins. diam., bears S.74\*E., 16 lks. dist., marked T 31 S R 1 W S 4 B T (Old B T.)

A fir, 15 ins. diam., bears S.88\*W., 14 lks. dist., marked T 31 S R 1 W S 5 B T (Old B T.)

A fir, 20 ins. diam., bears N.40\*E., 15 lks. dist., marked T 30 S R 1 W S 33 B T (Old B T.)

The old bearing tree in Sec. 32 is dead and fallen.