

County Surveyor's Record, Douglas County, Oregon

6707

Dependent Resurvey of Portion of South Boundary  
of T. 30 S., R. 1 W.

CHAINS

A cedar, 14 ins. diam., bears S.30\*E., 30 lks. dist.,  
marked  $\frac{1}{4}$  S 4 B T.

A fir, 10 ins. diam., bears S.39\*W., 55 lks. dist.,  
marked  $\frac{1}{4}$  S 4 B T.

40.96 The old  $\frac{1}{4}$  sec. cor., located by reference to the original  
bearing trees. From cor. point

A yew, 20 ins. diam., bears N.10\*E., 18 lks. dist.,  
marked  $\frac{1}{4}$  S B T (Old B T.)

A fir, 18 ins. diam., bears S.10\*W., 20 lks. dist.,  
marked  $\frac{1}{4}$  S B T (Old B T.)

I now change this cor. to refer to sec. 33 only, and ob-  
literate the marks on the bearing tree SW. of cor.

At exact cor. point

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the  
ground, for  $\frac{1}{4}$  sec. cor. of sec. 33 only, with brass  
cap marked

$\frac{1}{4}$  S33

1923

from which

A cedar, 12 ins. diam., bears N.60\*W., 19 lks.  
dist., marked  $\frac{1}{4}$  S 33 B T (New B T.)

Thence

S.89\*34'E.

0.41 Creek, 4 lks. wide, C. NE.

5.99 Creek, 5 lks. wide, C. NE.

7.59 Creek, 3 lks. wide, C. NE.

22.23 Creek, 2 lks. wide, C. NE.

37.04 Point of intersection of line bet. secs. 3 and 4, de-  
termined as hereinafter described.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in  
the ground, for closing cor. of secs. 3 and 4, with  
brass cap marked