

Dependent Resurvey of Portion of South Boundary
of T. 30 S., R. 1 W.

CHAINS

ft. high, for $\frac{1}{4}$ sec. cor. of sec. 34 only, with brass cap marked

$\frac{1}{4}$ S34
1923

from which

An oak, 15 ins. diam., bears N.58*E., 123 lks. dist., marked $\frac{1}{4}$ S 34 B T.

A fir, 24 ins. diam., bears N.13*W., 267 lks. dist., marked $\frac{1}{4}$ S 34 B T.

- 43.53 Leave rocky prairie, bears NW. and SE.
44.03 Draw, C. NE.; asc. 45 ft. over NW. slope.
45.71 Spur, slopes NE.; desc. 166 ft. over E. slope.
56.24 Beaver Creek, 25 lks. wide, C. NW.; asc. 236 ft. to sec. cor., over SW. slope.
60.93 Beaver Creek trail, bears NW. and SE.
77.79 Point of intersection of line bet. secs. 2 and 3, determined as hereinafter described.
Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for closing cor. of secs. 2 and 3, with brass cap marked

T30S R1W
S34
S3 | S2
T31S | R1W
CC
1923

from which

A fir, 40 ins. diam., bears S.24*E., 24 lks. dist., marked T 31 S R 1 W S 2 C C B T.

A fir, 38 ins. diam., bears S.27*W., 14 lks. dist., marked T 31 S R 1 W S 3 C C B T.

- 80.93 The old cor. of secs. 2, 3, 34 and 35, located by reference to the original bearing trees. From cor. point
An oak, 14 ins. diam., bears N.45*E., 51 lks. dist., marked T 30 S R 1 W S 35 B T (Old B T.)