

## County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of Portion of South Boundary  
of T. 30 S., R. 1 W.

CHAINS

Set an iron post, 3 ft. long, 1 ins. diam., 28 ins. in the ground, for  $\frac{1}{4}$  sec. cor. of sec. 2 only, with brass cap marked.

$\frac{1}{4}$  S2  
1923

from which

A fir, 7 ins. diam., bears S.8\*W., 87 lks. dist., marked  $\frac{1}{4}$  S 2 B T.

A fir, 12 ins. diam., bears S.51\*E., 149 lks. dist., marked  $\frac{1}{4}$  S 2 B T.

37.50 Creek, 2 lks. wide, C. SW.; asc. 166 ft. over NW. slope.

40.17 The old  $\frac{1}{4}$  sec. cor., located by reference to the original bearing trees. From cor. point

A fir, 30 ins. diam., bears N.88\*E., 73 lks. dist., marked  $\frac{1}{4}$  S B T (Old B T.)

A fir, 12 ins. diam., bears S.88\*E., 80 lks. dist., marked  $\frac{1}{4}$  S B T (Old B T.)

I now change this cor. to refer to sec. 35 only, and obliterate the marks on the bearing tree SE. of cor.

At exact cor. point

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for  $\frac{1}{4}$  sec. cor. of sec. 35 only, with brass cap marked

$\frac{1}{4}$  S35  
1923

from which

An oak, 8 ins. diam., bears N.18\*W., 66 lks. dist., marked  $\frac{1}{4}$  S 35 B T (New B T.)

Thence

N.89\*50'E.

1.87 Enter rocky prairie, bears NW. and SE.