

County Surveyor's Record, Douglas County, Oregon

Retracement and Dependent Resurvey of Portion of Subdivisional Lines in T. 30 S., R. 1 W.

CHAINS	<u>Retracement</u>
80.96	<p>Fall, 11 lks. E. of the old cor. of secs. 25, 26, 35 and 36.</p> <p>The bearing and length of the S. half mile is N.0*03'E., 40.29 chs., and of the N. half mile is N.0*12'W., 40.67 chs.</p> <p style="text-align: center;"><u>Resurvey</u></p> <p>From the cor. of secs. 35 and 36 only, on the S. bdy. of the Tp.,</p> <p>N.0*03'E., on a true line, on E. bdy. of sec. 35.</p> <p>Over mountainous land, through heavy timber and dense undergrowth.</p>
1.68	Draw, C. SE.; asc. 880 ft. over SW. slope.
9.50	Creek, 2 lks. wide, C. SW.
32.75	<p>Old Green Prairie-Beaver Lake trail on summit of divide between Beaver Creek and South Umpqua River bears E. and W.</p> <p>Descend 710 ft. over NE. slope.</p>
40.00	<p>Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for <math>\frac{1}{4}</math> sec. cor., for sec. 36 only, marked</p> <div style="text-align: center;"> <math>\frac{1}{4}</math>S36 1923         </div> <p style="text-align: right;">from which,</p> <p>A fir, 24 ins. diam., bears N.42'E., 77 lks. dist., marked <math>\frac{1}{4}</math> S 36 B T</p> <p>A cedar, 40 ins. diam., bears S.37'E., 46 lks. dist., marked <math>\frac{1}{4}</math> S 36 B T</p>
40.29	<p>The point for the <math>\frac{1}{4}</math> sec. cor. established for secs. 35 and 36, which I locate by reference to the original bearing trees. I now change this cor. to refer to sec. 35, only, and at the exact cor. point</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for <math>\frac{1}{4}</math> sec. cor., for sec. 35 only, marked</p>