

County Surveyor's Record, Douglas County, Oregon

Retracement and Dependent
Resurvey of Portion of Subdivisional Lines

in T. 30 S., R. 1 W.

CHAINS

1/4 S35
1923

from which

- A dead fir, 12 ins. diam., bears S.30*E., 40 lks. dist., marked 1/4 S B T: old B T. I destroy these marks.
- A dead fir, 9 ins. diam., bears N.45*W., 6 lks. dist., marked 1/4 S B T: old B T.
- A fir, 30 ins. diam., bears S.16*W., 49 lks. dist., marked 1/4 S 35 B T: new B T.
- A fir, 36 ins. diam., bears N.78*W., 52 lks. dist., marked 1/4 S 35 B T: new B T.

Thence

N.0*12*W.

Descend 160 feet to

- 10.36 Creek, 3 lks. wide, C. NW. Asc. 70 ft. over SW. slope.
- 17.08 Desc. 40 ft. over NW. slope.
- 29.64 Creek, 5 lks. wide, C. NW. Asc. 40 ft.
- 39.71 Set an iron post 3 ft. long, 2 ins. diam., 28 ins. in the ground for cor. of secs. 25 and 36 only, marked

S35 | T30S
 | S25
 |-----
 | S36
 | R1W
 | 1923

from which

- A fir, 8 ins. diam., bears N.23*E., 26 lks. dist., marked T 30 S R 1 W S 25 B T.
 - A cedar, 28 ins. diam., bears S.61*E., 24 lks. dist., marked T 30 S R 1 W S 36 B T.
 - 40.67 Top of spur slopes W.
- The cor. established for secs. 25, 26, 35 and 36, located by reference to the original bearing trees. The NE. bearing tree is dead, but standing, with marks still legible. The SE. and SW. trees are burned stubs and