

Retracement and Dependent Resurvey of Portion of
Subdivisional Lines in T. 30 S., R. 1 W.

CHAINS

Retracement

A fir, 16 ins. diam., bears N.60*E., 20 lks. dist.,
marked ¼ S 26 B T: old B T.

A fir, 16 ins. diam., bears S.60*E., 31 lks. dist.,
marked ¼ S 35 B T: new B T.

No iron post available for this corner.

42.00 Creek, 2 lks. wide, C. NW.

64.00 Asc. 50 ft. over NE. slope.

65.90 Top of divide bet. Beaver Creek and South Umpqua River,
bears NW. and SE.

Desc. 164 ft. over SW. slope.

80.03 Fall 11 lks. N. of the cor. of secs. 26, 27, 34, and 35,
located by reference to the original bearing trees,
which agree with the field notes except that the
bearing trees in secs. 26 and 34 are dead and fallen.

At exact corner point

Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in
the ground, for cor. of secs. 26, 27, 34 and 35 with
brass cap marked

T30S	R1W
S27	S26
S34	S35
1923	

from which

A cedar, 12 ins. diam., bears N.27*E., 70 lks.
dist., marked T 30 S R 1 W S 26 B T: new B T.

A fir, 28 ins. diam., bears S.75*E., 139 lks.
dist., marked T 30 S R 1 W S 35 B T: old B T.

A pine, 18 ins. diam., bears S.42*W., 83 lks.
dist., marked T 30 S R 1 W S 34 B T: new B T.

A fir, 24 ins. diam., bears N.2*W., 100 lks.
dist., marked T 30 S R 1 W S 27 B T: old B T.

The bearing and length of the E. half mile is N.89*43'W.,